GEKA® plus professional cleaning guns



Spare parts see chapter 11

GEKA® plus professional cleaning guns

Advantage / benefit:		compared to suitable for the German robust brass Ergonomic de the rubber-co the EPDM rub easy adjustm locking catch 23.1891.8 with with drinking	conventional cl drinking water, a drinking water of sign for fatigue-fr ated grip insulates ober coating is resi nent of the jet sp on the control lev GEKA® plus quick water th GEKA® plus pus	as the water-conducting components meet ordinance ombination guarantees long service life
Material:	housing: brass; valve insert: stainless steel; rubber coating: EPDM, blue			
Operating pressure:	max. 30 bar			
Temperature range:	max. 50 °C			
	seals for drinking water, DIN EN 16421 and KTW BWGL			
Jet type			c control lever at c	
Area of application:		0		al, commercial and agricultural applications
		•	-	[®] plus thread pieces and swivel joints
special note		with G1/2 ma		plus thread pieces and swiver joints
Weight:				
vveignt		approx. 800 g	J	
		GEKA [®] plus	GEKA® plus	
Connection	Female thread	quick coupling K	push-fit connector	
		drinking water	drinking water	
Female thread in mm	19.17			
Female thread	G1/2			
Flow volume at 3 bar l/min	17	17	17	23.1890.9
Flow volume at 5 bar l/min	21	21	21	23.1890.9
PU units	1	1	1	
Covering box units	12	12	12	
Item no.	23.1890.9	23.1891.8	46.7880.8	











From powerful rinsing to concentrated cleaning jet





Ó